

13.0 Zestawienie elementów studni inspekcyjnych DN 600PE

Nr studni	Rzędna w m.			Wysokość studni Hs	H1	H3	Typ kinety				H2	Typ rur [mm]	Pokrywa żeliwna D400
	Terenu	Dna studni	Wcięcia				1-P	2-DLiP	3-DP	4-DL			
2	3	4	5	6	7	8	9	10	11	12	13	14	15
S2	89,90	85,71	---	4,19	0,375	0,29	1				3,53	6000	1
S6	89,90	86,49	87,67	3,41	0,375	0,29	1				2,75	3000	1
S16	89,90	86,46	87,60	3,44	0,375	0,29	1				2,78	3000	1
S17	90,05	86,63	87,75	3,42	0,375	0,29	1				2,76	3000	1
S19	90,20	87,05	88,00	3,15	0,375	0,29	1				2,49	3000	1
S21	90,20	87,53	---	2,67	0,375	0,29	1				2,01	2000	1
S22	90,30	87,70	88,40	2,60	0,375	0,29	1				1,93	2000	1
S25	90,30	88,07	---	2,23	0,375	0,29				1	1,57	2000	1
S26	90,10	88,27	---	1,83	0,375	0,29				1	1,17	2000	1
S48	90,00	88,15	---	1,85	0,375	0,29				1	1,18	2000	1
S102	89,20	84,87	---	4,33	0,375	0,29	1				3,67	6000	1
S103	89,15	84,93	86,70/87,05	4,22	0,375	0,29	1				3,56	6000	1
S104	89,05	85,00	86,90	4,05	0,375	0,29	1				3,39	6000	1
S111	89,05	85,09	86,50	3,96	0,375	0,29	1				3,29	6000	1
S112	88,95	85,42	86,55	3,53	0,375	0,29	1				2,87	3000	1
S114	89,10	85,52	87,10/86,80	3,58	0,375	0,29	1				2,92	3000	1
S115	89,15	85,57	87,40	3,58	0,375	0,29	1				2,92	3000	1
S116	89,20	85,61	87,05	3,59	0,375	0,29	1				2,93	3000	1
S117	89,20	85,71	87,05/87,50	3,49	0,375	0,29	1				2,83	3000	1
S119	89,20	85,88	87,55	3,32	0,375	0,29	1				2,66	3000	1
S120	89,20	85,90	87,55	3,30	0,375	0,29	1				2,64	3000	1
S121	89,20	85,95	87,60	3,25	0,375	0,29	1				2,59	3000	1
S128	89,20	86,61	87,25	2,59	0,375	0,29	1				1,93	2000	1
S132	89,00	86,91	87,35	2,09	0,375	0,29	1				1,43	2000	1
S133	89,00	87,00	87,35	2,00	0,375	0,29	1				1,34	2000	1
S134	88,90	87,06	87,25	1,84	0,375	0,29	1				1,18	2000	1
S135	88,75	87,11	---	1,64	0,375	0,29		1			0,98	1000	1
S142	89,30	86,83	---	2,47	0,375	0,29				1	1,81	2000	1

S146	89,40	87,23	---	2,17	0,375	0,29			1		1,51	2000	1
S149	89,10	86,03	---	3,07	0,375	0,29	1				2,40	3000	1
S152	89,10	86,26	87,00/87,25	2,84	0,375	0,29	1				2,17	3000	1
S153	89,15	86,33	87,00	2,82	0,375	0,29	1				2,16	3000	1
S154	89,20	86,45	87,10	2,75	0,375	0,29	1				2,09	3000	1
S157	89,05	86,74	---	2,31	0,375	0,29				1	1,65	2000	1
S158	88,95	86,95	87,30	2,00	0,375	0,29				1	1,34	2000	1
S161	89,25	86,89	---	2,36	0,375	0,29	1				1,70	2000	1
S164	89,30	85,27	87,60	4,03	0,375	0,29	1				3,37	6000	1
S166	89,50	85,38	87,30/87,76	4,12	0,375	0,29	1				3,46	6000	1
S167	89,50	85,42	87,70	4,08	0,375	0,29	1				3,42	6000	1
S168	89,50	85,43	87,70	4,07	0,375	0,29	1				3,40	6000	1
S169	89,40	85,46	87,25	3,94	0,375	0,29	1				3,28	6000	1
S174	88,90	85,80	87,05	3,10	0,375	0,29	1				2,44	3000	1
S176	89,00	85,96	87,30	3,04	0,375	0,29	1				2,38	3000	1
S180	89,10	86,12	86,90	2,98	0,375	0,29	1				2,31	3000	1
S183	88,90	86,29	---	2,61	0,375	0,29		1			1,95	3000	1
S190	90,10	86,67	87,85	3,43	0,375	0,29	1				2,76	3000	1
S191	90,20	86,72	87,95/88,40	3,48	0,375	0,29	1				2,82	3000	1
S208	90,30	87,94	---	2,36	0,375	0,29				1	1,70	2000	1
S210	90,30	88,18	---	2,12	0,375	0,29				1	1,45	2000	1
S222	89,80	87,21	---	2,59	0,375	0,29			1		1,93	2000	1
S229	90,00	87,42	87,90/88,20	2,58	0,375	0,29	1				1,92	2000	1
S233	90,15	87,69	---	2,46	0,375	0,29		1			1,80	2000	1
S234	90,00	87,85	---	2,15	0,375	0,29		1			1,49	2000	1
S237	89,70	88,07	---	1,63	0,375	0,29		1			0,97	1000	1
S240	88,60	85,70	---	2,90	0,375	0,29		1			2,23	3000	1
S241	88,60	85,78	---	2,82	0,375	0,29		1			2,15	3000	1
S241/1	88,60	85,80	---	2,80	0,375	0,29	1				2,14	3000	1
S242	88,60	85,84	---	2,76	0,375	0,29		1			2,09	3000	1
S249	89,40	86,30	---	3,10	0,375	0,29		1			2,44	3000	1
S256	90,05	86,76	---	3,29	0,375	0,29			1		2,62	3000	1
S259	89,60	87,00	---	2,60	0,375	0,29		1			1,93	2000	1
S261	89,55	87,21	---	2,34	0,375	0,29			1		1,68	2000	1
S263	89,50	87,41	---	2,09	0,375	0,29		1			1,43	2000	1

S270	88,85	86,22	---	2,63	0,375	0,29			1		1,97	2000	1
S277	88,30	86,61	---	1,69	0,375	0,29			1		1,03	2000	1
S282	89,80	87,48	---	2,32	0,375	0,29				1	1,65	2000	1
S290	89,80	88,04	---	1,76	0,375	0,29			1		1,09	2000	1

40 11 7 9 149,3 67

Ilość studzienek		szt	67	Ilość rur karb. H=1000	szt.	2
Ilość kinet typ 1	przelot	szt	40	Ilość rur karb. H=2000	szt.	27
Ilość kinet typ 2	dopływ prawy i lewy	szt.	11	Ilość rur karb. H=3000	szt.	28
Ilość kinet typ 3	dopływ prawy	szt.	7	Ilość rur karb. H=6000	szt.	10
Ilość kinet typ 4	dopływ lewy	szt.	9	ilość pierścieni odciążających	szt.	67
				Pokrywa żeliwna typ ciężki	szt.	67